



SWIFT™ -XTRX

Flexible High-Performance X-Band Communications

Description

The SWIFT-XTRX is an X-band software defined transceiver that has one of the smallest size, weight and power form factors in the industry for its capabilities. As an integrated system, it combines the data interface, RF transceiver chain and power amplifier in a single package. With a wide array of electrical interfaces and AES encryption, the SWIFT-XTRX is suited to many different applications, from the Earth to the Moon and anything in between.



Why XTRX?



Low SWaP

Weighs < 1 kg and ~29W
Operating Power



Modulation Options

Tx and Rx can be modulated
based on your requirements

Modulation can be
configured on-orbit



Encrypted Networking

AES-256 can be added to
base configurations



Flight Heritage

Leverages SWIFT on-orbit
experience



Specifications

SDR Performance	Specification
Peak Throughput	Tx: Up to 100 Mbps (max 50 Mbps with HDLC framing) Rx: up to 5 Mbps
Frequency Range	Tx: 8 – 8.5 GHz Rx: 6.9 – 7.6 GHz
Tx Bandwidth	50 MHz
Tx Power	+33 dBm (Finely Adjustable)
Rx Bandwidth	9.9 MHz
Operating Dynamic Range	-120 to -50 dBm

Modulation Options- reconfigurable on-orbit

Rx	Tx
BPSK, AMFSK, SGLS, USB	BPSK, QPSK, OQPSK, 8PSK, 16APSK, SGLS, USB

SWaP	Specification
Size (with connectors and mounting feet)	(L) 107 x (W) 98 x (H) 62 mm
Mass	946 grams
Input Voltage	9 – 34.6 VDC
Operating Power	29 W
Standby Power	3 W
Operating Temperature	-30C to +60C
Radiation	40 Krad TID, 200 MeV non-destructive latch-up, rad-hard flash
Vibration	22.6 Grms

Interfaces

- RS-422 for TT&C (Prime and Redundant ports)
- LVDS for Data Transfer
- 1 Tx port SMA
- 1 Rx port SMA

Encryption (Optional Add-On)

- AES-256 up & down
- Compatible with KI-55, KI-103, Iron Fortress (KI-18x2)

Forward Error Correction

Convolutional Coding, Reed Solomon, LDPC, BCH

Features

- CCSDS TM/TC/AOS/Security Packet, Gryphon Framing
- NTIA/SFCG Mask Compliant
- PN Ranging (one-way, two-way)
- Coherent or non-coherent